






Flanged Fillers Model FIL



ANSI B16.1 Class 125



FILLER



BEVELED



REDUCING

Model FIL					
Nominal Size	Outside Diameter	Length - Weight			
		1"	2"	3"	4"
3	7.50	9	18	28	36
4	9.00	12	25	37	50
6	11.00	16	32	48	64
8	13.50	23	46	69	92
10	16.00	29	59	88	118
12	19.00	42	84	126	168
14	21.00	47	94	141	188
16	23.50	56	113	169	226
18	25.00	62	123	184	246
20	27.50	66	133	199	266
24	32.00	84	168	251	336
30	38.75	112	224	336	448
36	46.00	150	300	451	600
42	53.00	194	388	N/A	N/A
48	59.50	229	457	N/A	N/A

Flanged fillers are made to fit into piping locations shorter than the minimum length of fabricated pipe. Flanged fillers may be ordered to exact length and are faced on both sides.

Beveled Flanged Fillers are also available subject to manufacturing limitations and bolt clearance problems.

Reducing Flanged Fillers are also available for connecting flanged piping of two different diameters. (See Compact Reducer Flanges).

Material: Cast Iron to ASTM A48 (minimum 31,000 psi).
Ductile Iron to ASTM A536 (minimum 70,000 psi).

Form No. FP0200

Fab pipe inc.

011



21425 147th Ave. N., Rogers, MN 55374
Tel: (763) 428-2259 • Fax: (763) 428-4978

